

OFF GRID SX PLUS 10/25 LI



FEATURES:

- Li-Ion battery
- Automatic generator start/stopLow noise and emission
- Plug & Play
- Maintenance free
- Stackable (up to 2 units)



| Output specifications | | |
|---------------------------|-----|-----|
| Output power (Continuous) | kVA | 10 |
| Output power peak (5s) | kW | 20 |
| Voltage | V | 230 |
| Frequency | Hz | 50 |
| Phases | | 1 |



| Battery specifications | | |
|----------------------------------|--------|------------|
| Battery (Type) | | Li-ion LMN |
| Battery rated Voltage | V | 51.8 |
| Battery design life (to 80% DoD) | cycles | 3000 |
| Battery Nominal capacity (sizes) | kWh | 25 |
| Usable energy AC side (@80% DoD) | kWh | 20 |



General Description

SX Plus is a portable power unit that is noise emission and maintenance free. Energy that is stored within the internal battery is converted, electronically, into AC power. Once all the energy has been used up, the unit can be re-charged by one of several means; connecting to a mains power supply, from a conventional generator or, to be truly green, you can connect solar panels. You can use the unit while it is being charged.




| Input specifications | | |
|--|---|----|
| Maximum input Single Phase socket 230V | Α | 63 |
| System pass-through capacity | Α | 63 |







| Installation data | | |
|--|-------------|-------|
| Length | (L) mm 1096 | |
| Width | (W) mm | 1066 |
| Height | (H) mm | |
| Weight | kg | 560 |
| Protection rating | IP | 44 |
| Operating temperature range (charging suspended below 0°C) | °C | -1045 |



| Instruments, controls & connections | |
|---------------------------------------|-----------|
| Inverter protection Short Circuit | √ |
| Inverter protection Overload | √ |
| Inverter protection Over Temperature | V |
| Inverter protection Low Battery | √ |
| System status control panel | $\sqrt{}$ |
| Battery condition | √ |
| Battery main isolator | $\sqrt{}$ |
| Automatic generator auto-start signal | √ |
| Input MCB's | √ |
| Input 63A 230V IEC 60309 1ph | 1 |
| Output MCB's | √ |
| Output Protection RCBO 30mA | √ |
| Output 16A 230V Schuko | 1 |
| Output 16A 230V IEC 60309 1ph | 2 |
| Output 32A 230V IEC 60309 1ph | 1 |



BATTERY STORAGE DEPLOYED WITH GENERATOR TO SUPPLY SITE WELFARE UNIT



| Optional features | |
|---|------|
| Solar Kit Panel with External charge controller | • |
| Solar PV charge controller | MPPT |







