

### SURFACE PUMP DATA INFORMATION

PUMP TYPE	FIRE	CONTRACTOR	INDUSTRIAL	TRADE
Stock No		XSP9510	Retail Price	
Manufacturer		Godwin	Date In Stock	JUNE 22
Model		CD200M	Year of Manufacture	2012
Serial No		12610239/01	<b>CHASSIS</b>	
<b>PUMP DATA</b>			Open/ Skid	Canopy Skid
Max Flow		475m3/h	Sound Attenuated	Yes >70dBA at 9m
Max Head		45m	Length	2500mm
Suction Size - mm		8"	Width	1020mm
Suction Coupling Type		Female Bauer	Height	1600mm
Discharge Size - mm		8"	Colour	Dark Green
Discharge coupling Type		Male Bauer	Condition	Injection pipes need replacing prior to sale
Discharge Detail NRV/Gate/Gauge		NRV + Gauges		
Shaft Seal – Mech /Packing		Double Mechanical seal	<b>LIFTING DATA/ CHASSIS</b>	
Pump Speed Min/Max		1200-2100rpm	Weight Kg	Approx. 1400kg dry weight
Impeller Type – Open/Closed		Open	Centre Point	Yes
Impeller Size		280mm	Corner	No
Solids Handling - mm		80mm		
Others – Stages			Forklift	Yes on skid
Material			Trailer – Road tow	N/A
Priming Type Comp/vac/ventr		Compressor	Trailer – Site tow	N/A
Long/Close Coupled Pump		Close	Tow Bar Type	N/A
Belt Drive		Compressor connected to engine directly		
			<b>FUEL TANK DATA</b>	
<b>ENGINE DATA</b>			Size – Dimensions - approx	805 W x 1500 L x 200 H mm
Manufacturer		John Deere	Capacity	161litres
Model		4045DF290A	Gauge	Yes
Serial No		RS35521	Bunded	Yes 110% capacity
Hours		1735	Chassis	Integral
Exhaust Type		Std	Free Standing	
Bellows		No	Special	
Voltage		12v	<b>STARTER PANEL</b>	
Battery Type		Lead acid	Key / Button	Key
Battery Isolator		No	Hour Meter	Digital
Water Jacket Heater KW		No	Oil Pressure	Gauge
Cooling – Air – Rad - Exc		Radiator	Water Temp	gauge
<b>ELECTRIC MOTOR N/A</b>			Water Pressure	gauge
Make			Battery Amps	gauge
Voltage			Rev Counter	Gauge
KW			Special	
Amps			<b>COMMENTS</b>	
Cooling			FITTED WITH SOLAR BATTERY MAINTAINER	
Speed				
Foot / Flange				
Starter Type				