

T: 01953 454540 F: 01953 456968 E: enquiries@stuartgroup.info W: www.stuartgroup.co.uk

Stuart House, Hargham Road, Shropham, Norfolk NR17 1DT

SURFACE PUMP DATA INFORMATION

PUMP TYPE	FIRE			X	INDUSTRIAL	I	TRADE	
_	FINE	XSP6639	JONTRACIOR				INAUE	
Stock No					Retail Price		Ostabar 2022	
Manufacturer Model		SPP QI80			Date In Stock		October 2023	
Serial No				rear of	Year of Manufacture		CHASSIS	
PUMP				Onon/ G	Open/ Skid		Canopy	
Max Flow		120 M ³ /H			Sound Attenuated		Yes	
Max Head		89 M			Length		3900mm E	
Suction Size - mm		100mm			Width		1600mm E	
Suction Size - mm Suction Coupling Type								
		FEMALE BAUER 80mm		Height	Colour		1750mm E Black / White / Blue	
Discharge Size - mm								
Discharge coupling Type		FLANGE - BSP - F/H		Conditio	Condition		Average	
Discharge Detail NRV/Gate/Gauge		-						
Shaft Seal – Mech /Packing		Mech seal			LIFTING DATA/ CHASSIS			
Pump Speed Min/Max		1500 - 2400		Weight	Weight Kg		1350	
Impeller Type – Open/Closed		Closed		Centre	Centre Point		Yes	
Impeller Size		Full		Corner	Corner		Yes, in pipe frame	
Solids Handling		< 10mm						
Others – Stages		-		Forklift	Forklift		Yes	
Material		CGCI		Trailer -	Trailer – Road tow		Yes - No	
Priming Type Comp/vac/ventr		Vacuum		Trailer -	Trailer – Site tow		Yes	
Long/Close Coupled Pump		Long		Tow Ba	Tow Bar Type		Еуе	
Belt Drive		Vac pump						
					FUEL TANK DATA			
ENGINE DATA						Skid		
Manufacturer		Isuzu		Capacity	Capacity		220ltrs	
Model		4 Cyl 4LE1		Gauge	-		No	
Serial No		-		Bunded			Yes	
Hours		9,347		Chassis			Yes	
Exhaust Type		Internal		Free Sta	Free Standing		-	
Bellows		Yes		Special	Special		-	
Voltage		12 Volts			STARTER PANEL			
Battery Type		Lead Acid		Key / Bu	Key / Button		Yes	
Battery Isolator		-		Hour M	Hour Meter		Yes	
Water Jacket Heate	Water Jacket Heater KW -		-		Oil Pressure		-	
Cooling – Air – Rad - Exc		Water			Water Temp		-	
ELECTRIC MOTOR n/a			Water F	Water Pressure				
Make		N/A		Water \	/acuum	Yes		
Voltage		N/A		Rev Cou	Rev Counter		Yes	
KW		N/A		Special	Special		-	
Amps		N/A			Additional Comments.			
Cooling		N/A		Great for	Great for wellpoint jetting.			
Speed		N/A			High head - Pipe work - Fire main testing.			
Foot / Flange		N/A		High hea				
Starter Type		N/A						