

SURFACE PUMP DATA INFORMATION

PUMP TYPE	FIRE	CONTRACTOR	X	INDUSTRIAL		
Stock No		XSP4524	Retail Price		£POA	
Manufacturer		GODWIN	Date In Stock		JULY 2026	
Model		CD100M	Year of Manufacture		2008	
Serial No		S50857/03	CHASSIS			
PUMP DATA			Open/ Skid		SKID	
Max Flow		210 M³/HR	Sound Attenuated		YES	
Max Head		31 M	Length		1.95 M APPROX.	
Suction Size - mm		4” / 100 mm	Width		1.1 M APPROX.	
Suction Coupling Type		FEMALE BAUER TYPE	Height		1.5 M APPROX.	
Discharge Size - mm		4”/ 100 mm	Colour		ORANGE	
Discharge coupling Type		FLANGE (BS10 TABLE ‘D’)	Condition		USED	
Discharge Detail NRV/Gate/Gauge		DISCHARGE NRV				
Shaft Seal – Mech /Packing		MECHANICAL SEAL	LIFTING DATA/ CHASSIS			
Pump Speed Min/Max		1200 - 2000 RPM MAX	Weight Kg		1035 KG (DRY) APPROX	
Impeller Type – Open/Closed		OPEN	Centre Point		YES	
Impeller Size		220 mm	Corner		-	
Solids Handling		45 mm				
Others – Stages		SINGLE STAGE	Forklift		YES	
Material		CAST IRON CASING CAST STEEL IMPELLER	Trailer – Road tow		-	
Priming Type Comp/vac/ventr		COMPRESSOR/VENTURI AIR EJECTOR	Trailer – Site tow		-	
Long/Close Coupled Pump		CLOSE	Tow Bar Type		-	
Belt Drive		-				
			FUEL TANK DATA			
ENGINE DATA			Size - Dimensions		-	
Manufacturer		PERKINS	Capacity		145 LITRES (USABLE) APPROX.	
Model		403C-15	Gauge		-	
Serial No		HL35162U560431P	Bunded		-	
Hours		4263 HRS	Chassis		YES (INTEGRAL)	
Exhaust Type		SILENCER INTERNAL	Free Standing		-	
Bellows		-	Special		-	
Voltage		12V	STARTER PANEL			
Battery Type		LEAD ACID	Key / Button		KEY	
Battery Isolator		-	Hour Meter		YES (4263 HRS)	
Water Jacket Heater KW		-	Oil Pressure		YES	
Cooling – Air – Rad - Exc		WATER RADIATOR	Water Temp		YES	
ELECTRIC MOTOR			Water Pressure		-	
Make		-	Water Vacuum		-	
Voltage		-	Rev Counter		-	
KW		-	Special		AUTO STOP/START LEVEL CONTROL FITTED	
Amps		-	Additional Comments.			
Cooling		-	OFFERED WITH A RETURNED TO BASE WARRENTY OF 30- DAYS OR 250 HOURS WHICHEVER IS FIRST.			
Speed		-				
Foot / Flange		-				
Starter Type		-				