

SURFACE PUMP DATA INFORMATION

PUMP TYPE	FIRE	CONTRACTOR	X	INDUSTRIAL		
Stock No		XSP4525		Retail Price	£POA	
Manufacturer		GODWIN		Date In Stock	JULY 2026	
Model		CD100M		Year of Manufacture	2005	
Serial No		S39039/11		CHASSIS		
PUMP DATA			Open/ Skid	SKID		
Max Flow		210 M³/HR	Sound Attenuated	YES		
Max Head		31 M	Length	1.95 M APPROX.		
Suction Size - mm		4” / 100 mm	Width	1.1 M APPROX.		
Suction Coupling Type		FEMALE BAUER TYPE	Height	1.5 M APPROX.		
Discharge Size - mm		4”/ 100 mm	Colour	ORANGE		
Discharge coupling Type		FLANGE (BS10 TABLE ‘D’)	Condition	USED		
Discharge Detail NRV/Gate/Gauge		DISCHARGE NRV				
Shaft Seal – Mech /Packing		MECHANICAL SEAL	LIFTING DATA/ CHASSIS			
Pump Speed Min/Max		1200 - 2000 RPM MAX	Weight Kg	1035 KG (DRY) APPROX		
Impeller Type – Open/Closed		OPEN	Centre Point	YES		
Impeller Size		220 mm	Corner	-		
Solids Handling		45 mm				
Others – Stages		SINGLE STAGE	Forklift	YES		
Material		CAST IRON CASING CAST STEEL IMPELLER	Trailer – Road tow	-		
Priming Type Comp/vac/ventr		COMPRESSOR/VENTURI AIR EJECTOR	Trailer – Site tow	-		
Long/Close Coupled Pump		CLOSE	Tow Bar Type	-		
Belt Drive		-				
			FUEL TANK DATA			
ENGINE DATA			Size - Dimensions	-		
Manufacturer		PERKINS	Capacity	145 LITRES (USABLE) APPROX.		
Model		403C-15	Gauge	-		
Serial No		HL35162U524283L	Bunded	-		
Hours		24940 HRS	Chassis	YES (INTEGRAL)		
Exhaust Type		SILENCER INTERNAL	Free Standing	-		
Bellows		-	Special	-		
Voltage		12V	STARTER PANEL			
Battery Type		LEAD ACID	Key / Button	KEY		
Battery Isolator		-	Hour Meter	YES (24940 HRS)		
Water Jacket Heater KW		-	Oil Pressure	YES		
Cooling – Air – Rad - Exc		WATER RADIATOR	Water Temp	YES		
ELECTRIC MOTOR			Water Pressure	-		
Make		-	Water Vacuum	-		
Voltage		-	Rev Counter	-		
KW		-	Special	AUTO STOP/START LEVEL CONTROL FITTED		
Amps		-	Additional Comments.			
Cooling		-	OFFERED WITH A RETURNED TO BASE WARRENTY OF 30-DAYS OR 250 HOURS WHICHEVER IS FIRST.			
Speed		-				
Foot / Flange		-				
Starter Type		-				