

SURFACE PUMP DATA INFORMATION

| PUMP TYPE | FIRE | CONTRACTOR | INDUSTRIAL | X |
|------------------------------------|------|---|---|----------------------|
| Stock No | | SP9527 | Retail Price | £4,750-00 |
| Manufacturer | | WEIR | Date In Stock | APRIL 2026 |
| Model | | LNATEX IIIR | Year of Manufacture | - |
| Serial No | | L080D-3072 | CHASSIS | |
| PUMP DATA | | | Open/ Skid | OPEN |
| Max Flow | | 105 M ³ /H (@1600 RPM) | Sound Attenuated | - |
| Max Head | | 11 M (@1600 RPM) | Length | 1.0 M (APPROX) |
| Suction Size - mm | | 3" / 80 mm | Width | 1.0 M (APPROX) |
| Suction Coupling Type | | FLANGE BS 4504 (PN16) | Height | 0.6 M (APPROX) |
| Discharge Size - mm | | 3" / 80 mm | Colour | BLUE |
| Discharge coupling Type | | FLANGE BS 4504 (PN16) | Condition | USED - RECONDITIONED |
| Discharge Detail NRV/Gate/Gauge | | - | | |
| Shaft Seal – Mech /Packing | | DRY GLAND CASING | LIFTING DATA/ CHASSIS | |
| Pump Speed Min/Max | | 600 – 2100 RPM (SIZED TO RUN @ 1600 RPM) | Weight Kg | 440 KG (APPROX) |
| Impeller Type – Open/Closed | | CLOSED | Centre Point | YES |
| Impeller Size | | 254 mm | Corner | - |
| Solids Handling | | 15 mm | | |
| Others – Stages | | - | Forklift | - |
| Material | | CAST IRON | Trailer – Road tow | - |
| Priming Type Comp/vac/ventr | | - | Trailer – Site tow | - |
| Long/Close Coupled Pump | | OVERSLUNG MOTOR | Tow Bar Type | - |
| Belt Drive | | YES | | |
| ENGINE DATA | | | FUEL TANK DATA | |
| | | | Size - Dimensions | - |
| Manufacturer | | - | Capacity | - |
| Model | | - | Gauge | - |
| Serial No | | - | Bunded | - |
| Hours | | - | Chassis | - |
| Exhaust Type | | - | Free Standing | - |
| Bellows | | - | Special | - |
| Voltage | | - | STARTER PANEL | |
| Battery Type | | - | Key / Button | - |
| Battery Isolator | | - | Hour Meter | - |
| Water Jacket Heater KW | | - | Oil Pressure | - |
| Cooling – Air – Rad - Exc | | - | Water Temp | - |
| ELECTRIC MOTOR | | | Water Pressure | - |
| Make | | TECO S/N B8560020012 | Water Vacuum | - |
| Voltage | | 400 V | Rev Counter | - |
| KW | | 11 KW | Special | - |
| Amps | | 20.9 AMPS | Additional Comments. | |
| Cooling | | FAN | ELECTRIC MOTOR WITH PULLEYS SIZED TO RUN @1600 RPM. (LARGER ELECTRIC MOTORS OFFERED AT ADDITIONAL COST TO OFFER MORE FLOW AND DELIVERY HEAD) – POA. OFFERED WITH A UK RETURNED TO BASE WARRANTY OF 30- DAY. | |
| Speed | | 1460 RPM | | |
| Foot / Flange | | FOOT | | |
| Starter Type | | DOL | | |